

Model MIGI 502 D/M

INTEGRATED GENERATOR WITH COMPRESSOR

Engine	YANMAR mod. L 100
Power / RPM	7,0 kW (9,3 HP) / 3.000 rev/min
Fuel	Diesel
Fuel Tank	4,3 l
Fuel Consumption	1,8 l/h
Ignition	Electric
Cooling	Forced Air

GENERATORE DI CORRENTE

Alternator	115/230 V Single-Phase
Alternator	400 V Three-Phases (Optional)
Power / Frequency	6,8 kVA / 50 Hz
Power with AUX Service	2,5 kVA

COMPRESSOR

Compressor	Twin-Cylinders
Revolutions per Minute (RPM)	1,420 rev/min
Air Production	360 l/min – 22 m ³ /h
Max Pressure	10 Bar - 145 PSI
Internal Tank (Aluminium)	20 l
External Tank (Aluminium)	60 l (Optional)

GENERAL FEATURES

Dimensions L x W x H	1,100 x 640 x 750 mm
Weight (230 V Single-Phase)	220 kg
Weight (400 V Three-Phases)	230 kg
Noise Level	LWA 97 dB
Protection Class	IP 23



Model MIGI 502 D/M

60 l aluminum tank (Ø 310 x 1,000 mm, weight 12 kg) complete with quick connections, safety valve and pressure gauge

