Models MIGI 602 HBE OPEN and MIGI 602 LBE OPEN

INTEGRATED GENERATOR WITH COMPRESSOR – OPEN Version

Engine	HONDA mod. GX 390
Power / RPM	6,4 kW (8,6 HP) / 3.000 rev/min
Engine	LONCIN mod. G 420
Power / RPM	7,5 kW (10,1 HP) / 3.000 rev/min
Fuel	Gasoline
Fuel Tank	6,1 l
Fuel Consumption	2,5 l/h
Ignition	Electric
Cooling	Forced Air
Fume Exhaust	Positioned on the right side

GENERATOR

Alternator	115/230 V Single-Phase
Alternator	400 V Three-Phases (Optional)
Power / Frequency	5,0 kVA / 50Hz (Single-Phase)
Power / Frequency	6,0 kVA / 50Hz (Three-Phases + Single-Phase)
Power with AUX Service	1,0 kVA

COMPRESSOR

Compressor	Twin-Cylinders
Revolutions per Minute (RPM)	1,150 rev/min
Air Production	870 l/min – 52,2 m³/h
Max Pressure	11 bar – 160 PSI
Tank (Steel)	150 l

GENERAL FEATURES

Dimensions L x P X H	1,300 x 500 x 1,150 mm
Weight	210 kg
Protection Class	IP 23

Model MIGI 602 HBE/O